

Teknomer Butyl Insulating Tape

Self Adhesive Butyl Tape for Waterproofing



Public Pos. No: 04.013/1

Product Description Self adhesive butyl tape with PP carrier and silicone protection paper. It can stick many types of substrates.

Application Instructions It is used in waterproofing applications such as wet room (bathroom, balcony, terrace, roof, etc.), horizontal and vertical jointing and chamfering, shower room insulation and expense unit insulation, window blind casing insulation, self-adhesive butyl rubber coating before ceramic and natural stone applications it is easily applied. It is suitable for indoor use where non-pressurized water is exposed to moderate load (Ex. Residential bathrooms).

Material Composition Carrier: Polypropylene felt
Coating: Aging resistant, self-adhesive butyl rubber with high flexibility
Protection Layer: Two-piece silicone paper that can be easily separated.

Technical Data

| General Information | |
|-----------------------------------|--|
| Color | Gray |
| Resistance to Hotness, Min. /Max. | -5°C / +60°C |
| Item Width | 120mm ± 3mm |
| Product Thickness | 0,64mm ± 0,12mm |
| Product Range | 790g / m ² ± 35 g/m ² |
| Length of the Roll | 20m |
| Breaking Elongation | 60% transverse, 80% longitudinal |
| Application Recommendations | The protective paper is removed at an optimum temperature of not exceeding 28°C. |
| Storage | Store in cool, dry places that are not exposed to the sun rays. |
| Expires | The optimum usage period is 12 months. |